

DLPS-15DF SPECIFICATIONS

ELECTRICAL SPECIFICATIONS:

FREQUENCY: 5-1000 MHz

INSERTION LOSS:	GUARANTEED
5-40 MHz	>-40.0 dB
54-60 MHz	<1.5 dB
60-75 MHz	<1.0 dB
75-1000 MHz	<0.5 dB

RETURN LOSS:	GUARANTEED
54-60 MHz	>16 dB
60-75 MHz	>18 dB
75-1000 MHz	>18 dB

EMI SHIELDING:	>130 dB (5-1000 MHz)	
SWITCHING VOLTAGE:	135V Peak Min.	165V Max.
RESPONSE TIME:	Less than 1 nanosecond	
CURRENT SUPPRESSION:	500 Amps. (2 X 10 microsecond pulse)	

MECHANICAL SPECIFICATIONS:

DIMENSIONS:	2.35 in. W x 1.48 in. H x .64 in D
	59.7 mm W x 37.6 mm H x 16.26 mm D
OPERATING TEMPERATURE:	
(Ambient)	-40 to +140 Degrees Fahrenheit
	-40 to +60 Degrees Celsius (Centigrade)

THIS DOCUMENT IS THE PROPERTY OF CABLE INNOVATIONS. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

CABLE INNOVATIONS

130 STANLEY COURT LAWRENCEVILLE, GA 30045

PRODUCT SPECIFICATION, DLPS-15DF

DWG # 6215DF00 SHEET 1 REV A