

Power

AlphaPoint™

Optical Network Termination / Network Interface Unit Power Supply



12 Volt and 48 Volt versions available

- Provides clean, reliable power for ONT/NIDs
- Provides extended battery backup power during utility service interruption
- Built-in surge protection
- Replacement battery

Alpha introduces the AlphaPoint™, a cost-effective indoor power supply and UPS system for powering residential Customer Premise Equipment (CPE) providing cable telephony and fiber to the home (FTTH) advanced services. The AlphaPoint™ products provide continuous 12V or 48VDC locally to power these cable telephony or FTTH gateway devices such as Network Interface Units/Devices (NIU/NID) and Optical Network Termination (ONT) units. Extended runtime capabilities keep network communications, including telephone, up and running during power disturbances and outages.

AlphaPoint


Nominal Specifications

Electrical	
Input	
Voltage Range:	85 – 264
Frequency:	50 or 60 Hz
Output	
Voltage:	48V 12V
	48 VDC 12 VDC
Output Power Nominal:	15 W 18 W
Output Power Maximum:	25 W 35 W (<5 sec)
Transfer Characteristics:	Uninterrupted Uninterrupted
	Output Output
Battery	
Capacity:	7 AH
Type:	Sealed lead acid, maintenance free
Battery:	Temperature compensated
Backup Time (8 watt average):	8 hours
Recharge Time:	<24 hours
LED Indicators:	
	Output okay (green)
	Standby operation (green blinking)
	Low/Missing Battery (red blinking)
	Replace Battery (red)
Alarm Indicators:	
	AC FAIL (TELM 1)
	Replace Battery (TELM 2)
	Battery Missing (TELM 3)
	Battery Low (TELM 4)
	Note: Compliant with PacketCable™ UPS Specifications
	Embedded MTA Primary Line Support Specification
	PKT-SP-EMTA-Primary-101-001128

Mechanical	
Dimensions:	11"H x 7.5"W x 3.25"D (279.5mm x 190.5mm x 82.5mm)
Weight:	11 lbs (5 kg)

Environment	
Operating Temperature:	0° to 45° C
Storage Temperature:	- 15° to +45° C
Humidity:	0 to 95% relative
Mounting Configuration:	Wall mount
Agency Compliance:	FCC part 15 Class B CSA-NRTL\C CSA950

Warranty	
Electronic - all models:	2 years
Battery:	
Standard Life	2 years
Long Life	2 years



For contact information visit www.AGIPower.com

The Alpha Group >		Europe, Middle East & Africa	Asia Pacific	North America	Latin & South America
Cyprus	Germany	Australia	Canada	Contact USA office	
Tel: +357 25 375 675	Tel: +49 9122 79889 0	Tel: +61 2 9722 3320	Tel: +1 604 430 1476		
Fax: +357 25 359 595	Fax: +49 9122 79889 21	Fax: +61 2 9722 3321	Fax: +1 604 430 8908		
Russia	United Kingdom	P.R. China	USA		
Tel: +7 095 925 9844	Tel: +44 1279 422110	Tel: +852 2736 8663	Tel: +1 360 647 2360		
Fax: +7 095 916 1349	Fax: +44 1279 423355	Fax: +852 2199 7988	Fax: +1 360 671 4936		