

PLS-125P SPECIFICATIONS

ELECTRICAL SPECIFICATIONS:

LINE VOLTAGE	120VAC
MAX CONTINUOUS VOLTAGE	130VAC
PEAK CURRENT	25kA
RESPONSE TIME	Less than 1 nanosecond
FREQUENCY	50,60,400 Hz
MAXIMUM CLAMPING VOLTAGE @ 100A	340VAC
ENERGY (10/1000us)	336 Joules
VARISTOR VOLTAGE @ 1mA	200V
MAX LEAKAGE CURRENT	Less than 1mA
PROTECTION	L-N-G

MECHANICAL SPECIFICATIONS:

DIMENSIONS:	2.97 in. L x 1.97 in. W x 2.05 in H
OPERATING TEMPERATURE:	
(Ambient)	-40 to +140 Degrees Fahrenheit
	-40 to +60 Degrees Celsius (Centigrade)

THIS DOCUMENT IS THE PROPERTY OF CABLE INNOVATIONS. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

CABLE INNOVATIONS

130 STANLEY COURT LAWRENCEVILLE, GA 30045

PRODUCT SPECIFICATION, PLS-125P

DWG # 62125P00 SHEET 1 REV A