

PLS-220Z SPECIFICATIONS

ELECTRICAL SPECIFICATIONS:

LINE VOLTAGE	220VAC
MAX CONTINUOUS VOLTAGE	250VAC
PEAK CURRENT	80kA
RESPONSE TIME	Less than 1 nanosecond
FREQUENCY	50,60,400 Hz
MAXIMUM CLAMPING VOLTAGE @ 100A	650VAC
ENERGY (10/1000us)	2200 Joules
VARISTOR VOLTAGE @ 1mA	390V
MAX LEAKAGE CURRENT	Less than 1mA

MECHANICAL SPECIFICATIONS:

DIMENSIONS:	1.65 in. W x 4.1 in. H x 1.65 in D
	41.9 mm W x 104.1 mm H x 41.9 mm D
WIRING	14awg 18" Length
OPERATING TEMPERATURE:	
(Ambient)	-40 to +140 Degrees Fahrenheit
	-40 to +60 Degrees Celsius (Centigrade)

THIS DOCUMENT IS THE PROPERTY OF CABLE INNOVATIONS. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

CABLE INNOVATIONS

130 STANLEY COURT LAWRENCEVILLE, GA 30045

PRODUCT SPECIFICATION, PLS-220Z

DWG # 62220Z00 SHEET 1 REV A